

Chicago Metallic® Drywall Grid



LEED® v4.1 Highlights

Materials and Resources (MR)

Waste Management Planning	✓
Interiors Life Cycle Impact Reduction	✓
Environmental Product Declarations	✓
Sourcing of Raw Materials	✓
Material Ingredients	-
Waste Management	✓

Indoor Environmental Quality (EQ)




Low-Emitting Materials	✓
Interior Lighting	✓

Recycled Content 30%

Performance Properties:

Base Material	Hot-Dip Galvanized Steel (HDG-40)
Capping	Knurled Face Hot-Dip Galvanized Steel (HDG-40)
End Details	Main Runners: Bayonet-End Coupling Cross Tees: Stab-End, Hook-End
Structural Classification	Heavy Duty per ASTM C635
Flame Spread Rating	Class A per ASTM E84
Warranty	40-Year Suspension System Warranty
Recycled Content	30%

Main Runners/Cross Tees

Detail	Product Number	Length x Height (A) x Face (B)	Grid Coupling Type	Slotting	Structural Classification (ASTM C635)	Fire-Rated	Seismic	Packaging			Palletization	
								Pcs/Ctn	LF/Ctn	Lbs/Ctn	Ctn/Pallet	Lbs/Pallet
Main Runners												
	640.00C	144" x 1-1/2" x 1-3/8"	Bayonet-End	8" OC	HD	-	A-F	20	240	86	28	2408
	650.00C	144" x 1-1/2" x 1-3/8"	Bayonet-End	8" OC	HD	✓	A-F	20	240	86	28	2408
	Notched Main Runner for Field Curving											
	640.00CR	144" x 1-1/2" x 1-3/8"	Bayonet-End	8" OC	HD	-	A-F	20	240	86	28	2408
Cross Tees												
	644.00C	48" x 7/8" x 1-3/8"	Hook-End	1 Slot at Midpoint	-	-	A-C	40	160	46	30	1380
	654.00C	48" x 1-1/2" x 1-3/8"	Hook-End	No Slots	-	✓	A-C	40	160	47	30	1410
	664.00C	48" x 7/8" x 1-3/8"	Stab-End	1 Slot at Midpoint	-	-	A-F	40	160	40	30	1200
	674.00C	48" x 1-1/2" x 1-3/8"	Stab-End	1 Slot at Midpoint	-	✓	A-F	40	160	47	30	1410
	677.00C	72" x 7/8" x 1-3/8"	Stab-End	24 OC	-	✓	A-F	20	120	43	Palletized to Order	2394
	1274.01Z	48" x 1-1/2" x 15/16"	Stab-End	3 Slots 12" OC	-	✓	A-F	60	240	73.2	30	2196

Custom slotting available. Contact Rockfon Customer Service for details and service levels.